
## NSN 3020-00-678-6386

Helical Gear - Page 1 of 2





#### **Pitch Diameter:**

6.5520 inches

## **Teeth Quantity:**

65

## Bore Style:

Tapered w/keyway first end

## Hardness Rating:

285.0 brinell standard and 325.0 brinell standard

#### **Outside Diameter:**

6.724 inches

#### **Teeth Type:**

Single helix

#### Tooth Form:

Standard

#### Tooth Direction:

Left

#### **Helix Angle:**

30.0483 degrees

## Distance Between Body Face And Protruding Hub End:

0.375 inches first end

## Distance Between Body Face And Recessed Hub End:

0.500 inches second end

## Face Width:

1.750 inches

#### Keyway Width:

0.376 inches both ends

## Distance From Bore Center To Keyway Bottom:

1.639 inches both ends

#### **Taper Major Diameter:**

1.868 inches first end

#### Hub Style Designator:

Plain second end

#### Hub Diameter:

2.500 inches second end

Material:

Steel

## Material Specification:

Mil-s-890, alloy no. 4 military specification single material response

## Style Designator:

One protruding hub, one recessed hub

## Shelf Life:

N/a

# NSN 3020-00-678-6386

Helical Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-890 spec.

