NSN 3020-00-679-9548

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-679-9548

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 2.5000 inches |
| Teeth Quantity: |
| 80 |
| Bore Style: |
| W/counterbore both ends |
| Mounting Hole Type And Quantity: |
| 6 plain axially through body, first end |
| Outside Diameter: |
| 2.564 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.093 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 1.657 inches both ends |
| Counterbore Depth: |
| 0.156 inches second end |
| Counterbore Diameter: |
| 1.718 inches second end |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 2.250 inches first end |
| Mounting Hole Diameter: |
| 0.225 inches axially through body, first end |
| Special Features: |
| Unthreaded holes spaced 60 degrees apart |
| Material: |
| Plastic phenolic |
| Material Specification: |
| Mil-p-15035, type fbe military specification single material response |
| Style Designator: |
| Protruding hub |

NSN 3020-00-679-9548

Spur Gear - Page 2 of 2



| N/a | |
|---------|----------|
| Unit Of | Measure: |
| | |

Shelf Life:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-p-15035 spec.