NSN 3020-00-682-3867

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-682-3867

Attachment Method:
Internal ring groove
Pitch Diameter:
3.1250 inches
Teeth Quantity:
150
Outside Diameter:
3.1666 inches
Nominallength:
1.530 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.875 inches first end
Face Width:
0.104 inches
Hub Style Designator:
2 steps first end
End Length:
0.538 inches first end
End Diameter:
0.310 inches both ends
First Step Length:
0.267 inches first end
First Step Diameter:
0.500 inches second end
Second Step Length:
0.070 inches first end
Second Step Diameter:
0.880 inches first end
Special Features:
0.280 in.Clamping surface Ig on both hub ends and 0.060 in.Wide 0.298 in. Diameter grooves on both ends, 0.250 in.From end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

NSN 3020-00-682-3867

Spur Antibacklash Gear - Page 2 of 2



Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-a-8625 spec.