NSN 3020-00-684-1696

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-684-1696

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.3125 inches
Teeth Quantity:
105
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
1.337 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.202 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.015 inches first end
Precision Classification:
Quality number 12
End Diameter:
0.281 inches first end
First Step Length:
0.183 inches first end
First Step Diameter:
First Step Diameter:

0.468 inches first end

NSN 3020-00-684-1696 Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Copper alloy
Material Specification:
Astm-b-139 type b1 assn standard single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No