NSN 3020-00-684-1696

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-684-1696

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.3125 inches **Teeth Quantity:** 105 **Bore Style:** Plain both ends **Backlash Designation:** Grade c Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 1.337 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.202 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.187 inches both ends Hub Style Designator: 1 step first end End Length: 0.015 inches first end **Precision Classification:** Quality number 12 End Diameter: 0.281 inches first end First Step Length: 0.183 inches first end **First Step Diameter:** 0.468 inches first end

NSN 3020-00-684-1696

Spur Gear - Page 2 of 2



Material:

Copper alloy

Material Specification:

Astm-b-139 type b1 assn standard single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300