NSN 3020-00-690-2936



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-690-2936 **Body Style:** Plain, solid **Pitch Diameter:** Between 0.3712 inches and 0.3731 inches **Teeth Quantity:** 24 **Bore Style:** Plain both ends **Outside Diameter:** 0.401 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.297 inches first end **Face Width:** 0.281 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.401 inches first end **Special Features:** 0.157 in.Min, 0.158 in.Max w slot @across second end of gear Material: Steel comp 1018 or steel comp 1020 **Material Specification:** 66 federal standard all material responses or aisi/sae 1018 assn standard 1st material response or aisi/sae 1020 assn standard 2nd material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 2 military specification single treatment response

Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 3020-00-690-2936

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-c-13924 spec.