NSN 3020-00-691-4403

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-691-4403

Body Style: Webbed, offset, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 5.7500 inches **Teeth Quantity:** 276 **Bore Style:** Tapered first end **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end Mounting Hole Thread Size: 0.312 inches transversely through hub, first end Mounting Hole Type And Quantity: 3 threaded transversely through hub, first end **Outside Diameter:** 5.792 inches Nominallength: 0.828 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.672 inches first end **Body Recess Depth:** 0.156 inches second end Face Width: 0.156 inches **Taper Major Diameter:** 3.062 inches both ends Hub Style Designator: 1 step first end End Length: 0.444 inches first end End Diameter: 3.687 inches first end First Step Length: 0.228 inches first end

NSN 3020-00-691-4403

Spur Gear - Page 2 of 2



First Step Diameter:

4.438 inches first end

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300