## NSN 3020-00-692-4858

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-692-4858

View Online at https://aerobasegroup.com/nsn/3020-00-692-
Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
7.1875 inches
Teeth Quantity:
115
Bore Style:
W/ keyway both ends
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Mounting Hole Type And Quantity:
3 plain transversely through hub, first end
Outside Diameter:
7.309 inches
Nominallength:
1.245 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.653 inches first end
Body Recess Depth:
0.171 inches second end
Face Width:
0.594 inches
Bore Diameter:
0.501 inches both ends
Keyway Width:
0.096 inches both ends
Distance From Bore Center To Keyway Bottom:
0.298 inches both ends
Counterbore Depth:
0.146 inches second end
Counterbore Diameter:
2.234 inches second end
Hub Style Designator:
1 step first end
End Length:

0.531 inches first end

## NSN 3020-00-692-4858

Spur Gear - Page 2 of 2



**End Diameter:** 0.750 inches first end First Step Length: 0.122 inches first end First Step Diameter: 4.062 inches first end Mounting Hole Diameter: 0.391 inches axially through hub, first end **Bolt Hole Circle Diameter:** 3.375 inches axially through hub, first end Material: Steel **Material Specification:** Mil-s-13048 military specification single material response **Style Designator:** Protruding hub, recessed body Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A27300 Mil-std (military Standard): Mil-s-13048 spec.