## NSN 3020-00-692-4860



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-692-4860 **Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole Pitch Diameter: 6.1250 inches **Teeth Quantity:** 98 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unf axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 24 axially through hub, first end **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Mounting Hole Thread Size:** 0.375 inches axially through hub, first end **Mounting Hole Type And Quantity:** 3 threaded axially through hub, first end **Outside Diameter:** 6.249 inches Nominallength: 0.873 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.467 inches first end **Body Recess Depth:** 0.188 inches second end **Face Width:** 0.406 inches

**Bore Diameter:** 2.441 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 

4.000 inches first end

**Bolt Hole Circle Diameter:** 

3.374 inches axially through hub, first end

## **NSN 3020-00-692-4860** Spur Gear - Page 2 of 2

A27300



Material:
Steel comp 1141
Material Specification:
66 federal standard single material response and aisi/sae 1141 assn standard single material response
Style Designator:
Protruding hub, recessed body
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: