NSN 3020-00-692-9240

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-692-9240

| D. I. O. I. |
|---|
| Body Style: |
| Plain, solid |
| Spline Quantity: |
| 33 both ends |
| Pitch Diameter: |
| 4.7500 inches |
| Teeth Quantity: |
| 19 |
| Bore Style: |
| Involute spline both ends |
| Spline Pitch Diameter: |
| 2.0625 inches both ends |
| Hardness Rating: |
| 60.0 rockwell c |
| Outside Diameter: |
| 5.290 inches |
| Nominallength: |
| 2.154 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 25.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.200 inches both ends |
| Face Width: |
| 1.750 inches |
| Bore Diameter: |
| 2.154 inches both ends |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 2.500 inches both ends |
| Material: |
| Steel comp 8620 |
| Material Specification: |
| Qq-5-624 federal specification single material response |
| |
| Style Designator: |
| Protruding hubs Shelf Life: |
| N/a |
| N/a |

--

NSN 3020-00-692-9240

Spur Gear - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A27300