NSN 3020-00-695-7285

Groove Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-695-7285

Counterbore Diameter:
2.500 inches
Counterbore Depth:
1.656 inches
Groove Depth:
0.625 inches
Groove Width:
Between 0.498 inches and 0.502 inches
Outside Diameter:
Between 7.370 inches and 7.380 inches
Overall Length:
3.656 inches
Keyway Width:
Between 0.251 inches and 0.253 inches
Thread Size:
5/16 - 18
Bore Diameter:
Between 1.6885 inches and 1.6895 inches
Bore Length:
3.656 inches
Distance From Center Of Bore To Bottom Of Keyway:
Between 0.964 inches and 0.969 inches
V Groove Angle In Deg:
36.0
Pitch Diameter:
6.750 inches
Securing Hole Quantity:
6
Furnished Items And Quantity:
N/a
Material And Location:
Material And Location:
Material And Location: Iron
Material And Location: Iron Face Width:
Material And Location: Iron Face Width: 2.500 inches
Material And Location: Iron Face Width: 2.500 inches Design Form:
Material And Location: Iron Face Width: 2.500 inches Design Form: Webbed
Material And Location: Iron Face Width: 2.500 inches Design Form: Webbed Bore Type:

Groove Quantity:

NSN 3020-00-695-7285

Groove Pulley - Page 2 of 2



Counterbore Feature:
Included
Counterbore Location:
Bb end
Hole Location:
Located on 3-3/4 in. Bolt circle
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Threaded hole
Split Hub Feature:
Not included
Web/spoke Relationship To Face Centerline:
Offset
Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Groove Shape:
V
Bore Feature:
Included
Securing Location:
Bb end
Hub End Outside Diameter And Location:
2.500 inches aa end and 3.122 inches bb end and 3.124 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
1.031 inches aa end and 0.125 inches bb end
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a