

View Online at <https://aerobasegroup.com/nsn/3020-00-695-7285>

Counterbore Diameter:

2.500 inches

Counterbore Depth:

1.656 inches

Groove Depth:

0.625 inches

Groove Width:

Between 0.498 inches and 0.502 inches

Outside Diameter:

Between 7.370 inches and 7.380 inches

Overall Length:

3.656 inches

Keyway Width:

Between 0.251 inches and 0.253 inches

Thread Size:

5/16 - 18

Bore Diameter:

Between 1.6885 inches and 1.6895 inches

Bore Length:

3.656 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.964 inches and 0.969 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

6.750 inches

Securing Hole Quantity:

6

Furnished Items And Quantity:

N/a

Material And Location:

Iron

Face Width:

2.500 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

3

Counterbore Feature:

Included

Counterbore Location:

Bb end

Hole Location:

Located on 3-3/4 in. Bolt circle

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Securing Location:

Bb end

Hub End Outside Diameter And Location:

2.500 inches aa end and 3.122 inches bb end and 3.124 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

1.031 inches aa end and 0.125 inches bb end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a