

View Online at <https://aerobasegroup.com/nsn/3020-00-696-0206>

Groove Depth:

0.490 inches

Groove Width:

0.490 inches

Outside Diameter:

4.500 inches

Overall Length:

1.375 inches

Bore Diameter:

Between 0.501 inches and 0.502 inches

Bore Length:

0.766 inches

Drilled Hole Diameter:

0.144 inches

V Groove Angle In Deg:

34.0

Pitch Diameter:

Between 4.000 inches and 4.400 inches

Securing Hole Quantity:

2

Furnished Items And Quantity:

Bore bushing, one each

Material And Location:

Steel

Face Width:

0.625 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

Centered0.344 in. From end of hub, 180 degs apart

Keying Facility:

Not included

Securing Method:

Drilled hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

3I and 4I

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Aa end

Hub End Outside Diameter And Location:

0.875 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.609 inches bb end

First Step Face Largest Diameter And Location:

2.531 inches aa end

Second Step Face Largest Diameter And Location:

3.500 inches aa end

First Step Length And Location:

0.625 inches aa end

Second Step Length And Location:

0.062 inches aa end

Third Step Length And Location:

0.062 inches aa end

Hub End Outside Diameter And Location:

1.125 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.750 inches aa end

Surface Treatment:

Paint

Style Designator:

Webbed or spoked

Surface Treatment:

Painted

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a