NSN 3020-00-698-5705

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-698-5705

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
4.0000 inches
Teeth Quantity:
128
Bore Style:
W/ keyway both ends
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end
Outside Diameter:
4.062 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
1.374 inches first end
Face Width:
0.188 inches
Bore Diameter:
0.500 inches both ends
Keyway Width:
0.094 inches both ends
Distance From Bore Center To Keyway Bottom:
0.549 inches both ends
Hub Style Designator:
2 grooves first end
Hub Diameter:
0.750 inches first end
First Groove Width:
0.125 inches first end
First Groove Diameter:
0.664 inches first end
Distance From End To First Groove:
0.500 inches first end
Second Groove Width:
0.031 inches first end
Second Groove Diameter:

0.755 inches first end

NSN 3020-00-698-5705

Spur Gear - Page 2 of 2

No Fiig: A27300



Distance From End To Second Groove:
0.937 inches first end
Mounting Hole Diameter:
0.375 inches transversely through hub, first end
Special Features:
Counterbore on 1st end w/ 2.000 in. Dia, 0.125 in. Depth
Material:
Copper alloy
Material Specification:
Qq-b-721, class b, temper 1/2 hard federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: