## NSN 3020-00-698-6076

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-698-6076

Body Style:
Plain, solid
Pitch Diameter:
0.5000 inches
Teeth Quantity:
12
Hardness Rating:
50.0 rockwell c and 55.0 rockwell c
Outside Diameter:
0.607 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.781 inches first end
Face Width:
0.500 inches
Hub Style Designator:
3 steps second end
End Length:
0.250 inches second end
End Diameter:
0.315 inches second end
First Step Length:
0.553 inches first end
First Step Diameter:
0.379 inches second end
Second Step Length:
0.063 inches second end
Second Step Diameter:
0.405 inches second end
Third Step Length:
0.313 inches second end
Third Step Diameter:
0.407 inches second end
Material:
Steel
Material Specification:
Qq-s-624-canc federal specification single material response
Surface Treatment:

Passivate

## NSN 3020-00-698-6076

Spur Gear - Page 2 of 2



Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:

Unit Of Measure:
-Demilitarization:

No

N/a

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.