NSN 3020-00-699-7999

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-699-7999

Body Style:

Webbed, solid

Spline Quantity:

15 both ends

Attachment Method:

Mounting hole

Pitch Diameter:

3.8333 inches

Teeth Quantity:

23

Bore Style:

W/counterbore second end

Spline Pitch Diameter:

0.9375 inches both ends

Hardness Rating:

60.0 rockwell c

Mounting Hole Type And Quantity:

1 plain transversely through hub, first end

Outside Diameter:

4.164 inches

Nominallength:

0.870 inches

Tooth Form:

Standard

Pressure Angle:

25.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.400 inches first end

Face Width:

0.470 inches

Bore Diameter:

1.000 inches second end

Counterbore Depth:

0.300 inches first end

Counterbore Diameter:

1.140 inches first end

Hub Style Designator:

1 groove first end

Hub Diameter:

1.560 inches first end

End Diameter:

1.560 inches first end

NSN 3020-00-699-7999 Spur Gear - Page 2 of 2



| First Groove Width: |
|--|
| 0.140 inches first end |
| First Groove Diameter: |
| 1.370 inches first end |
| Distance From End To First Groove: |
| 0.130 inches first end |
| Mounting Hole Diameter: |
| 0.125 inches axially through hub, first end |
| Material: |
| Steel comp 8620 |
| Material Specification: |
| -s-13048 military specification single material response |
| Style Designator: |
| One protruding hub, one flush hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |
| Mil-std (military Standard): |
| spec. |