

View Online at <https://aerobasegroup.com/nsn/3020-00-704-9476>

Counterbore Diameter:

Between 17.375 inches and 17.380 inches

Counterbore Depth:

Between 0.250 inches and 0.260 inches

Outside Diameter:

24.922 inches

Bolt Circle Diameter:

15.876 inches

Bore Diameter:

Between 14.313 inches and 14.438 inches

Bore Length:

1.000 inches

Pitch Diameter:

22.816 inches

Securing Hole Quantity:

13

Face Width:

1.000 inches

Design Form:

Plain

Bore Type:

Straight

Metallic Hardness Rating And Location:

55.0 rockwell c body and 60.0 rockwell c body

Counterbore Feature:

Included

Counterbore Location:

Aa end

Hole Location:

Centerline of teeth

Keying Facility:

Not included

Securing Method:

Drilled hole

Lightening Hole:

Not included

Tapered Hole Size:

0.640 to 0.6425

Belt/chain/film Size For Which Designed:

Track

Teeth Row Quantity:

1

Teeth Quantity Per Row:

13

Hardness Rating Test Method:

Rockwell

Teeth Hardness Rating:

Between 55.0 rockwell c and 60.0 rockwell c

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

5.514 inches

Material:

Steel, qq-s-624, comp fs4150-canceled and steel, qq-s-624, comp fs8645-canceled and steel, qq-s-624, fs8650-canceled and steel, qq-s-624, comp fs8750-canceled and steel, qq-s-624, comp fs9445-canceled

Material:

Steel comp 4150 and steel, qq-s-624, comp fs8645-canceled and steel comp 8650 and steel comp 8750 and steel comp 9445

Material Specification:

Qq-s-624, comp fs4150-canceled federal specification 1st material response and qq-s-624, fs8650-canceled federal specification 3rd material response and qq-s-624, comp fs8750-canceled federal specification 4th material response and qq-s-624, comp fs9445-canceled federal specification 5th material response

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T353-c