NSN 3020-00-705-2646

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-705-2646 **Body Style:** Plain, solid Pitch Diameter: 0.7500 inches **Teeth Quantity:** 18 **Bore Style:** W/ keyway both ends **Features Provided:** Casehardened **Outside Diameter:** 0.8333 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Face Width:** 0.6250 inches **Bore Diameter:** 0.4378 inches both ends **Keyway Width:** 0.1265 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.2836 inches both ends **Special Features:** No surface treatment on bore Material: Steel **Material Specification:** Mil-s-8690, cond c, surface cond 4 military specification single material response **Surface Treatment:** Lubricant dry film and phosphate **Surface Treatment Specification:** Mil-I-25504 military specification 1st treatment response and mil-p-16232, type m, class 2 military specification 2nd treatment response **Style Designator:** Hubless Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 3020-00-705-2646

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-s-8690 spec.