NSN 3020-00-706-3034

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-706-3034 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.5333 inches **Teeth Quantity:** 16 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.600 inches Nominallength: 0.422 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.297 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.188 inches both ends **Hub Diameter:** 0.438 inches first end Material: Copper alloy 360 **Material Specification:** Qq-b-626, alloy 360, 1/2h federal specification single material response **Surface Treatment:** Chromium **Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Style Designator:** Protruding hub

N/a

Shelf Life:

NSN 3020-00-706-3034

Spur Gear - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.