

View Online at <https://aerobasegroup.com/nsn/3020-00-708-8143>

**Groove Depth:**

0.625 inches

**Groove Width:**

0.4375 inches

**Outside Diameter:**

7.563 inches

**Overall Length:**

3.000 inches

**Keyway Width:**

Between 0.188 inches and 0.189 inches

**Bore Diameter:**

Between 0.751 inches and 0.752 inches

**Bore Length:**

1.500 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.465 inches

**V Groove Angle In Deg:**

36.0

**Pitch Diameter:**

5.312 inches

**Material And Location:**

Aluminum alloy, qq-a-601, class 3m and aluminum alloy, qq-a-596, class 8

**Face Width:**

1.375 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Taper Major Diameter Location:**

Aa end

**Groove Quantity:**

2

**Counterbore Feature:**

Not included

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Split Hub Feature:**

Included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Hub Split Location:**

Through one wall

**Clamping Bolt Quantity:**

1

**Hub End Outside Diameter And Location:**

2.031 inches aa end and 1.250 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

1.625 inches aa end

**Quantity:**

1

**Surface Treatment:**

Hard coat, sandford process

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Hard coat, sandford process

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T353-a