

View Online at <https://aerobasegroup.com/nsn/3020-00-708-8143>

Groove Depth:

0.625 inches

Groove Width:

0.4375 inches

Outside Diameter:

7.563 inches

Overall Length:

3.000 inches

Keyway Width:

Between 0.188 inches and 0.189 inches

Bore Diameter:

Between 0.751 inches and 0.752 inches

Bore Length:

1.500 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.465 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

5.312 inches

Material And Location:

Aluminum alloy, qq-a-601, class 3m and aluminum alloy, qq-a-596, class 8

Face Width:

1.375 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Taper Major Diameter Location:

Aa end

Groove Quantity:

2

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Split Hub Feature:

Included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Hub Split Location:

Through one wall

Clamping Bolt Quantity:

1

Hub End Outside Diameter And Location:

2.031 inches aa end and 1.250 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

1.625 inches aa end

Quantity:

1

Surface Treatment:

Hard coat, sandford process

Style Designator:

Webbed or spoked

Surface Treatment:

Hard coat, sandford process

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T353-a