NSN 3020-00-711-6052

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-711-6052

Dada Otala
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.7500 inches
Teeth Quantity:
84
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
1.792 inches
Nominallength:
0.343 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.218 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10
Material:
material.

Aluminum alloy 2024

NSN 3020-00-711-6052

Spur Gear - Page 2 of 2

A27300

Mil-a-8625 spec.

Mil-std (military Standard):



Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: