NSN 3020-00-713-9957

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-713-9957

| Counterbore Diameter: |
|---|
| 0.500 inches |
| Counterbore Depth: |
| 0.032 inches |
| Outside Diameter: |
| 0.875 inches |
| Overall Length: |
| 0.250 inches |
| Bore Diameter: |
| 0.374 inches |
| Bore Length: |
| 0.250 inches |
| Pitch Diameter: |
| 0.895 inches |
| Face Width: |
| 0.076 inches |
| Guide: |
| Not included |
| Design Form: |
| Webbed |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Included |
| Lubrication Mode: |
| Self-impregnated or no visible means |
| Counterbore Location: |
| Both ends |
| Keying Facility: |
| Not included |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Plain |
| Belt/chain/film Size For Which Designed: |
| Silent chain |
| Roller Chain Pitch Type For Which Designed: |
| Single pitch |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |

15

NSN 3020-00-713-9957 Sprocket Wheel - Page 2 of 2



| Plain Surface Treatment: Passivated Shelf Life: | ardness Rating Test Method: |
|---|--|
| Included Hub External Keyway: Not included Tooth Pitch: 0.188 inches Hub End Outside Diameter And Location: 0.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | ot rated |
| Hub External Keyway: Not included Tooth Pitch: 0.188 inches Hub End Outside Diameter And Location: 0.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | ore Bearing: |
| Not included Tooth Pitch: 0.188 inches Hub End Outside Diameter And Location: 0.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | cluded |
| Tooth Pitch: 0.188 inches Hub End Outside Diameter And Location: 0.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | ub External Keyway: |
| O.188 inches Hub End Outside Diameter And Location: 0.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | ot included |
| Hub End Outside Diameter And Location: 0.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | ooth Pitch: |
| O.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | .188 inches |
| Distance From Outside Flange/rim To Hub End And Location: 0.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | ub End Outside Diameter And Location: |
| O.087 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | .625 inches both ends |
| Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | istance From Outside Flange/rim To Hub End And Location: |
| Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | .087 inches both ends |
| Material: Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | aterial: |
| Stainless steel Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | teel, corrosion resisting |
| Surface Treatment: Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | aterial: |
| Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: | tainless steel |
| Style Designator: Plain Surface Treatment: Passivated Shelf Life: | urface Treatment: |
| Surface Treatment: Passivated Shelf Life: | assivate |
| Surface Treatment: Passivated Shelf Life: | tyle Designator: |
| Passivated Shelf Life: | lain |
| Shelf Life: | urface Treatment: |
| | assivated |
| N. 1. | helf Life: |
| N/a | /a |
| Unit Of Measure: | nit Of Measure: |
| | |
| Demilitarization: | emilitarization: |
| No | 0 |
| Fiig: | iig: |
| T353-c | 353-c |