## NSN 3020-00-720-3260



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-720-3260 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.2500 inches **Teeth Quantity:** 40 **Bore Style:** W/counterbore second end **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.1120 inches axially through body, first end **Mounting Hole Type And Quantity:** 1 plain axially through body, first end and 1 threaded axially through body, first end **Outside Diameter:** 1.3125 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees Distance Between Body Face And Protruding Hub End: 0.1590 inches first end **Face Width:** 0.0620 inches **Bore Diameter:** 0.2510 inches first end **Counterbore Depth:** 0.1400 inches second end **Counterbore Diameter:** 0.3950 inches second end **Hub Style Designator:** Plain first end **Hub Diameter:** 0.3325 inches first end

End Length: 0.0180 inches

0.0180 inches second end

**End Diameter:** 

0.5070 inches second end

First Step Length:

0.0695 inches second end

## NSN 3020-00-720-3260

Spur Gear - Page 2 of 2



First Step Diameter:
0.5615 inches second end
Mounting Hole Diameter:
0.0475 inches axially through body, first end
Bolt Hole Circle Diameter:
0.9620 inches axially through body, first end
Special Features:
1 0.048 in. Diameter plain hole and 1 0.112 in. Diameter threaded hole on first end hub for postioniing
Material:
Copper alloy
Material Specification:
Qq-b-626, comp 22, 1/2h federal specification single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300