## NSN 3020-00-720-3545

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-720-3545

·
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.5000 inches
Teeth Quantity:
48
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.520 inches
Nominallength:
0.281 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.189 inches first end
Face Width:
0.092 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.313 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:

Aluminum alloy 2024

## NSN 3020-00-720-3545

Spur Gear - Page 2 of 2

A27300

Mil-a-8625 spec.

Mil-std (military Standard):



## Material Specification: Qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Protruding hub Shelf Life: N/a Unit Of Measure: -- Demilitarization: No Fiig: