NSN 3020-00-724-7404



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-724-7404 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.6250 inches **Teeth Quantity:** 75 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 80 transversely through hub, first end **Mounting Hole Thread Size:** 0.060 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.642 inches Nominallength: 0.190 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.113 inches first end **Face Width:** 0.077 inches **Bore Diameter:** 0.120 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.250 inches first end **Special Features:** Mtg holes 90 degs apart Material: Steel comp 303 **Material Specification:**

Qq-s-763, class303 federal specification single material response

NSN 3020-00-724-7404

Spur Gear - Page 2 of 2



_	•		_			
<u>ن</u>	irta	\sim	Irο	atm	nan	
υı	ai ia	ᅜ	116	аш		ı.,

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300