NSN 3020-00-725-2535

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-725-2535

Body Style: Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.3333 inches **Teeth Quantity:** 96 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.361 inches Nominallength: 0.375 inches Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.505 inches first end **Special Features:** Mounting holes located 120 degrees apart Material: Aluminum alloy 2024 **Material Specification:** Qq-a-268 federal specification single material response

Surface Treatment:

Anodize

NSN 3020-00-725-2535

Spur Gear - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Mil-a-8625 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.