## NSN 3020-00-726-2944

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-726-2944 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.6250 inches **Teeth Quantity:** 30 **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees Distance Between Body Face And Protruding Hub End: 0.230 inches first end **Face Width:** 0.145 inches **Bore Diameter:** 0.188 inches both ends **Hub Diameter:** 0.438 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 416se **Material Specification:** Qq-s-764, type 416se, cond a federal specification single material response **Surface Treatment: Passivate Style Designator:** Protruding hub

Shelf Life: N/a

## NSN 3020-00-726-2944

Spur Gear - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A27300