## NSN 3020-00-727-7967

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-727-7967

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.5625 inches **Teeth Quantity:** 100 **Bore Style:** Plain both ends **Backlash Designation:** Grade c Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 1.594 inches Nominallength: 0.312 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.125 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 0.313 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material:

Aluminum alloy 2024

## NSN 3020-00-727-7967

Spur Gear - Page 2 of 2



Material Specification:

Qq-a-225/6, t4 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300