NSN 3020-00-728-1005

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-728-1005

Outside Diameter:
3.084 inches
Overall Length:
0.852 inches
Bore Diameter:
0.515 inches
Bore Length:
0.852 inches
Pitch Diameter:
2.948 inches
Face Width:
0.107 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
26.0 rockwell c body and 36.0 rockwell c body
Counterbore Feature:
Not included
Keying Facility:
Not included
Lightening Hole:
Included
Protruding Hub Characteristic:
Stepped
Groove/step Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
37
Asa Standard Chain Number:
25
Hardness Rating Test Method:
naranoss nating rest method.

Rockwell

NSN 3020-00-728-1005 Sprocket Wheel - Page 2 of 2



Teeth Hardness Rating:
Between 26.0 rockwell c and 36.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.250 inches
Hub End Outside Diameter And Location:
0.787 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.745 inches both ends
First Step Face Largest Diameter And Location:
0.940 inches both ends
Second Step Length And Location:
0.283 inches both ends
Material:
Steel, qq-s-763, class 410
Material:
Steel comp 410
Material Specification:
Qq-s-763, class 410 federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c