## NSN 3020-00-729-6663

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-00-729-6663

Webbed, offset, with lightening holes						
Spline Quantity:						
14 both ends						
Attachment Method:						
Mounting hole						
Pitch Diameter:						
2.1250 inches						
Teeth Quantity:						
68						
Bore Style:						
Involute spline both ends						
Spline Pitch Diameter:						
0.2917 inches both ends						
Hardness Rating:						
30.0 rockwell c and 38.0 rockwell c						
Mounting Hole Type And Quantity:						
2 plain transversely through hub, first end						
Outside Diameter:						
2.170 inches						
Nominallength:						
0.450 inches						
Tooth Form:						
Standard						
Pressure Angle:						
20.0000 degrees						
Distance Between Body Face And Protruding Hub End:						
0.240 inches first end						
Face Width:						
0.210 inches						
Bore Diameter:						
0.292 inches both ends						
Hub Style Designator:						
Plain first end						
Hub Diameter:						
0.495 inches first end						
Mounting Hole Diameter:						
0.098 inches transversely through hub, first end						
Material:						
Steel comp 416se						
Material Specification:						
Ams 5610 assn standard single material response						

## NSN 3020-00-729-6663

Spur Gear - Page 2 of 2



$\overline{}$			-			
<b>~</b> I	ırfa	ഫ	ırc	natr	nΔn	

Passivate

**Style Designator:** 

One protruding hub, one flush hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300