NSN 3020-00-732-1239



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-732-1239 **Outside Diameter:** 2.688 inches **Overall Length:** 1.125 inches **Keyway Width:** 0.251 inches **Thread Size:** 1/4 in. -20 **Bore Diameter:** 1.000 inches **Bore Length:** 1.125 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.625 inches **Pitch Diameter:** 2.563 inches **Securing Hole Quantity:** Face Width: 0.259 inches **Design Form:** Plain **Bore Type:** Straight **Metallic Hardness Rating And Location:** 45.0 rockwell c body and 50.0 rockwell c body **Counterbore Feature:** Not included **Hole Location:** Located in hubs top of keyway, 0.500 in from end of hub to centerline of hole **Keying Facility:** Included **Keying Facility Type:**

Keyway

Securing Method:
Threaded hole
Lightening Hole:
Not included

Belt/chain/film Size For Which Designed:
Roller chain

Roller Chain Pitch Type For Which Designed:
Single pitch

NSN 3020-00-732-1239 Sprocket Wheel - Page 2 of 2



Teeth Row Quantity:
1
Teeth Quantity Per Row:
16
Asa Standard Chain Number:
40
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 45.000 rockwell c and 50.000 rockwell c
Bore Bearing:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
1.969 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.860 inches aa end
Material:
Steel, aisi c1141 and steel, aisi 1141
Material:
Steel comp 1141 and steel comp 1141
Material Specification:
Aisi c1141 assn standard 1st material response and aisi 1141 assn standard 2nd material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c