## NSN 3020-00-734-3450

Bevel Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-734-3450

| Body Style:  |
|--|
| Plain, solid   |
| Attachment Method:   |
| Mounting hole  |
| Pitch Diameter:  |
| 0.2500 inches  |
| Teeth Quantity:  |
| 16   |
| Bore Style:  |
| Plain both ends  |
| Hardness Rating:   |
| 34.0 rockwell c and 38.0 rockwell c                        |
| Mounting Hole Type And Quantity:                           |
| 1 plain transversely through hub, first end                |
| Outside Diameter:  |
| 0.2910 inches  |
| Nominallength:   |
| 0.300 inches   |
| Teeth Type:  |
| Straight   |
| Pressure Angle:  |
| 20.0000 degrees  |
| Pitch Angle:   |
| 13.0000 degrees  |
| Face Width:  |
| 0.142 inches   |
| Bore Diameter:   |
| 0.124 inches both ends                                     |
| Hub Style Designator:                                      |
| Plain first end  |
| Hub Diameter:  |
| 0.210 inches first end                                     |
| Mounting Hole Diameter:                                    |
| 0.041 inches transversely through hub, first end           |
| Material:  |
| Steel comp 4130  |
| Material Specification:                                    |
| Mil-s-6758 military specification single material response |
| Surface Treatment:   |
| Oxide  |
| Style Designator:  |
| Peripheral face back hub protruding                        |

## NSN 3020-00-734-3450

Bevel Gear - Page 2 of 2



| N/a               |  |
|-------------------|--|
| Unit Of Measure:  |  |
|                   |  |
| Demilitarization: |  |
| No                |  |
| Fiig:             |  |
| A27300            |  |

Mil-std (military Standard):

Mil-s-6758 spec.

Shelf Life: