NSN 3020-00-735-0079

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-735-0079

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.3333 inches **Teeth Quantity:** 160 **Bore Style:** Plain both ends **Backlash Designation:** Grade c Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 1.350 inches Nominallength: 0.250 inches Tooth Form: Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.188 inches first end Face Width: 0.062 inches **Bore Diameter:** 0.125 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 0.312 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material:

Aluminum alloy 2024

NSN 3020-00-735-0079

Spur Gear - Page 2 of 2



Material Specification: Qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 military specification single treatment response Style Designator: Protruding hub Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A27300 Mil-std (military Standard): Mil-a-8625 spec.