NSN 3020-00-735-1158

Bevel Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-735-1158

| Body Style: |
|---|
| Plain, solid |
| Pitch Diameter: |
| 3.8462 inches |
| Teeth Quantity: |
| 25 |
| Bore Style: |
| Plain both ends |
| Hardness Rating: |
| 58.0 rockwell c teeth and 62.0 rockwell c teeth |
| Outside Diameter: |
| 3.9759 inches |
| Nominallength: |
| 0.294 inches |
| Teeth Type: |
| Straight |
| Pressure Angle: |
| 20.0000 degrees |
| Pitch Angle: |
| 55.7841 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.060 inches second end |
| Face Width: |
| 0.720 inches |
| Bore Diameter: |
| 0.936 inches both ends |
| Bore Depth: |
| 2.940 inches both ends |
| Counterbore Depth: |
| 0.8500 inches first end |
| Counterbore Diameter: |
| 1.250 inches first end |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 2.060 inches second end |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-13048, fs8615, fs8620, fs8720 military specification single material response |
| Style Designator: |

Peripheral face, protruding hubs

NSN 3020-00-735-1158

Bevel Gear - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Shelf Life:

Fiig:

A27300

Mil-std (military Standard):

Mil-s-13048 spec.