# NSN 3020-00-735-3646

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-735-3646

# Body Style:

Plain, solid

**Pitch Diameter:** 

0.2812 inches

# Teeth Quantity:

18

### Bore Style:

Plain both ends

#### Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

### **Outside Diameter:**

0.313 inches

#### Tooth Form:

Standard

#### Flange Diameter:

0.875 inches

#### \_\_\_\_

Pilot Length:

# 0.188 inches

# Pressure Angle:

20.0000 degrees

# Flange Thickness:

0.030 inches

# Face Width:

0.140 inches

#### **Bore Diameter:**

0.192 inches both ends

### Distance Between Outer Body Face And Inner Flange Face:

0.169 inches

#### Hub Diameter:

0.235 inches between body and flange

#### Pilot Diameter:

0.374 inches

#### **Special Features:**

Bore is flatten ontwo sides

#### Material:

Steel

# Material Specification:

Mil-s-6709, cond a military specification single material response

# Surface Treatment:

Oxide

### Surface Treatment Specification:

Mil-c-13924, class 2 military specification single treatment response

# NSN 3020-00-735-3646

Spur Gear - Page 2 of 2

Style Designator:

Flanged end with pilot

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-6709 spec.

