## NSN 3020-00-735-8823



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-735-8823 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.4166 inches **Teeth Quantity:** 30 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.444 inches Nominallength: 0.343 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.218 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end

Precision Classification:
Quality number 12
Material:
Steel comp 303

## NSN 3020-00-735-8823

Spur Gear - Page 2 of 2

No Fiig: A27300



Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: