## NSN 3020-00-736-2202

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-736-2202

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 3.1875 inches **Teeth Quantity:** 204 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end Mounting Hole Thread Size: 0.112 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 3.218 inches **Tooth Form:** Standard Pressure Angle: 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.188 inches both ends Hub Style Designator: 1 step first end End Length: 0.188 inches first end End Diameter: 0.500 inches first end First Step Length: 0.063 inches first end **First Step Diameter:** 0.875 inches first end Material: Aluminum alloy 2024

## NSN 3020-00-736-2202

Spur Gear - Page 2 of 2



**Material Specification:** 

Qq-a-225/6, t4 federal specification single material response

## Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

**Demilitarization:** No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.