NSN 3020-00-736-3814

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-736-3814

| Body Style: |
|---|
| Plain, solid |
| Pitch Diameter: |
| 1.0000 inches |
| Teeth Quantity: |
| 48 |
| Bore Style: |
| Plain both ends |
| Hardness Rating: |
| 25.0 rockwell c |
| Outside Diameter: |
| 1.040 inches |
| Nominallength: |
| 0.625 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.313 inches first end |
| Face Width: |
| 0.312 inches |
| Bore Diameter: |
| 0.469 inches both ends |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.062 inches first end |
| Precision Classification: |
| Quality number 6 |
| End Diameter: |
| 0.612 inches first end |
| First Step Length: |
| 0.251 inches first end |
| First Step Diameter: |
| 0.750 inches first end |
| Material: |
| Steel comp 416 |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |

Passivate

NSN 3020-00-736-3814

Spur Gear - Page 2 of 2



| Surface Treatment Speci |
|-------------------------|
|-------------------------|

171, finish no. 5.4.1 military standard single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300