NSN 3020-00-738-4296



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-738-4296 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.0625 inches **Teeth Quantity:** 198 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.081 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 416 **Material Specification:**

Qq-s-763, class416 federal specification single material response

NSN 3020-00-738-4296

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-std-171 spec.



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300