## NSN 3020-00-739-3842

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-739-3842

| Body Style:   |
|---|
| Webbed, solid   |
| Attachment Method:  |
| Slot  |
| Pitch Diameter:   |
| 1.1093 inches   |
| Teeth Quantity:   |
| 71  |
| Bore Style:   |
| Plain both ends   |
| Outside Diameter:   |
| 1.141 inches  |
| Nominallength:  |
| 0.343 inches  |
| Tooth Form:   |
| Standard  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Distance Between Body Face And Protruding Hub End:  |
| 0.157 inches first end  |
| Face Width:   |
| 0.093 inches  |
| Bore Diameter:  |
| 0.120 inches both ends  |
| Hub Style Designator:   |
| 1 groove both ends  |
| Hub Diameter:   |
| 0.249 inches second end   |
| First Groove Width:   |
| 0.050 inches first end  |
| First Groove Diameter:  |
| 0.220 inches second end   |
| Distance From End To First Groove:  |
| 0.107 inches first end  |
| Special Features:   |
| Four slots, 0.031 in. W by 0.157 in. Lg, spaced 90 degrees apart on 0.187 in. Diameter bolt circle on 1st hub end |
| Material:   |
| Steel comp 303  |
| Material Specification:   |
| Qq-s-763, class 303, cond a federal specification single material response  |
| Surface Treatment:  |
| Passivate   |

## NSN 3020-00-739-3842

Spur Gear - Page 2 of 2



| •     | _   |      |        |
|-------|-----|------|--------|
| Style | De: | sıar | nator: |
| ,     |     | 9.9. |        |

Protruding hubs

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300