## NSN 3020-00-740-5523



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-740-5523 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.5000 inches **Teeth Quantity:** 72 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.164 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.542 inches Nominallength: 0.563 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.313 inches first end **Face Width:** 0.250 inches **Bore Diameter:** 0.375 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.750 inches first end **Special Features:** Mtg holes 90 degrees apart Material: Steel comp 416 **Material Specification:** 

Qq-s-763, class416 federal specification single material response

## NSN 3020-00-740-5523

Spur Gear - Page 2 of 2



| _        | •    |        | _   |   |    |    |  |
|----------|------|--------|-----|---|----|----|--|
| <u>ن</u> | urfa | $\sim$ | l r | 2 | ŀm | Δn |  |
|          |      |        |     |   |    |    |  |

Passivate

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300