NSN 3020-00-740-5533

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-740-5533

Pady Styles						
Body Style: Plain, solid						
Attachment Method:						
Mounting hole						
Pitch Diameter:						
0.7500 inches						
Teeth Quantity: 24						
Bore Style:						
Plain both ends						
Backlash Designation:						
Grade b						
Mounting Hole Thread Series Designator:						
Unc transversely through hub, first end						
Mounting Hole Thready Qty Per Inch (tpi):						
32 transversely through hub, first end						
Mounting Hole Thread Size:						
0.164 inches transversely through hub, first end						
Mounting Hole Type And Quantity:						
2 threaded transversely through hub, first end						
Outside Diameter:						
0.810 inches						
Nominallength:						
0.437 inches						
Tooth Form:						
Standard						
Pressure Angle:						
14.5000 degrees						
Distance Between Body Face And Protruding Hub End:						
0.250 inches first end						
Face Width:						
0.187 inches						
Bore Diameter:						
0.375 inches both ends						
Hub Style Designator:						
Plain first end						
Hub Diameter:						
0.625 inches first end						
Precision Classification:						
Quality number 10 or quality number 11						
Material:						

Stainless steel

NSN 3020-00-740-5533

Spur Gear - Page 2 of 2



$\overline{}$			-			
<u>ن</u>	irto	2	Iro	atn	าคท	

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300