

View Online at <https://aerobasegroup.com/nsn/3020-00-741-1971>

Outside Diameter:

2.500 inches

Overall Length:

Between 0.875 inches and 0.877 inches

Key Width:

0.250 inches

Thread Size:

14 in. - 20

Bore Diameter:

Between 0.985 inches and 0.986 inches

Bore Length:

Between 0.875 inches and 0.877 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.617 inches and 0.618 inches

Pitch Diameter:

2.247 inches

Securing Hole Quantity:

1

Face Width:

0.281 inches

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Located 90 degrees from keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Stepped

Groove/step Location:

Aa end

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

14

Asa Standard Chain Number:

41

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

0.500 inches

Hub End Outside Diameter And Location:

1.312 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.594 inches both ends and 0.596 inches both ends

First Step Face Largest Diameter And Location:

16.687 inches both ends

First Step Length And Location:

0.062 inches both ends

Material:

Steel, qq-s-633, fs1045-canceled

Material:

Steel comp 1045

Material Specification:

Qq-s-633, fs1045-canceled federal specification single material response

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-c