

View Online at <https://aerobasegroup.com/nsn/3020-00-752-1901>

Groove Depth:

0.625 inches

Groove Width:

0.625 inches

Outside Diameter:

6.406 inches

Overall Length:

3.563 inches

Keyway Width:

Between 0.126 inches and 0.128 inches

Thread Size:

5/16-18

Bore Diameter:

Between 0.667 inches and 0.668 inches

Bore Length:

Between 1.1875 inches and 1.1975 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.377 inches and 0.3875 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

6.063 inches

Securing Hole Quantity:

6

Material And Location:

Iron, cast, sae 110

Face Width:

1.875 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

Located, equally spaced on 2-3/8 bolt circle

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

A

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Aa end

First Step Face Largest Diameter And Location:

3.000 inches aa end

First Step Length And Location:

0.250 inches aa end

Hub End Outside Diameter And Location:

1.057 inches aa end and 1.059 inches aa end and 3.000 inches aa end and 1.188 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

1.688 inches aa end and 2.375 inches bb end

Special Features:

6 ribs on id of pulley, 1/16 in. Deep counterbore on od of face at bb end of gear

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

T353-a