NSN 3020-00-753-0990

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-753-0990 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.2778 inches **Teeth Quantity:** 46 **Bore Style:** W/ keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 40 axially through body, first end **Mounting Hole Thread Size:** 0.112 inches axially through flange **Mounting Hole Type And Quantity:** 2 threaded axially through body, first end **Outside Diameter:** 1.331 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.069 inches first end **Face Width:** 0.157 inches **Bore Diameter:** 0.375 inches both ends **Keyway Width:** 0.063 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.222 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.625 inches first end **Precision Classification:**

Quality number 8

Bolt Hole Circle Diameter:

0.875 inches axially through body, first end

NSN 3020-00-753-0990

Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Steel comp 303
Material Specification:
$\ensuremath{Qq}\text{-s-763},$ class 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No