NSN 3020-00-753-0990

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-753-0990

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.2778 inches **Teeth Quantity:** 46 **Bore Style:** W/ keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 40 axially through body, first end Mounting Hole Thread Size: 0.112 inches axially through flange Mounting Hole Type And Quantity: 2 threaded axially through body, first end **Outside Diameter:** 1.331 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.069 inches first end Face Width: 0.157 inches **Bore Diameter:** 0.375 inches both ends **Keyway Width:** 0.063 inches both ends Distance From Bore Center To Keyway Bottom: 0.222 inches both ends Hub Style Designator: Plain first end Hub Diameter: 0.625 inches first end **Precision Classification:** Quality number 8 **Bolt Hole Circle Diameter:**

0.875 inches axially through body, first end

NSN 3020-00-753-0990

Spur Gear - Page 2 of 2



Material:

Steel comp 303

Material Specification:

Qq-s-763, class 303, cond a federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300