

View Online at <https://aerobasegroup.com/nsn/3020-00-753-8613>

**Counterbore Diameter:**

2.125 inches

**Counterbore Depth:**

0.0625 inches

**Groove Depth:**

0.625 inches

**Groove Width:**

0.625 inches

**Outside Diameter:**

7.125 inches

**Overall Length:**

3.063 inches

**Keyway Width:**

Between 0.251 inches and 0.253 inches

**Bore Diameter:**

Between 1.7495 inches and 1.7505 inches

**Bore Length:**

2.125 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 0.9973 inches and 1.0075 inches

**V Groove Angle In Deg:**

38.5

**Pitch Diameter:**

6.609 inches

**Material And Location:**

Iron, qq-i-666, grade 2

**Face Width:**

1.594 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Included

**Counterbore Location:**

Bb end

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

B

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Stepped

**First Step Face Largest Diameter And Location:**

2.609 inches aa end

**First Step Length And Location:**

1.406 inches aa end

**Hub End Outside Diameter And Location:**

2.370 inches aa end and 2.380 inches aa end and 2.744 inches bb end and 2.748 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

1.469 inches aa end and 0.938 inches bb end

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a