

View Online at <https://aerobasegroup.com/nsn/3020-00-753-8613>

Counterbore Diameter:

2.125 inches

Counterbore Depth:

0.0625 inches

Groove Depth:

0.625 inches

Groove Width:

0.625 inches

Outside Diameter:

7.125 inches

Overall Length:

3.063 inches

Keyway Width:

Between 0.251 inches and 0.253 inches

Bore Diameter:

Between 1.7495 inches and 1.7505 inches

Bore Length:

2.125 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.9973 inches and 1.0075 inches

V Groove Angle In Deg:

38.5

Pitch Diameter:

6.609 inches

Material And Location:

Iron, qq-i-666, grade 2

Face Width:

1.594 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Included

Counterbore Location:

Bb end

Keying Facility:

Included

Keying Facility Type:

Keyway

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

B

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

First Step Face Largest Diameter And Location:

2.609 inches aa end

First Step Length And Location:

1.406 inches aa end

Hub End Outside Diameter And Location:

2.370 inches aa end and 2.380 inches aa end and 2.744 inches bb end and 2.748 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

1.469 inches aa end and 0.938 inches bb end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a