NSN 3020-00-753-9882

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-753-9882

Webbed, offset, solid
Spline Quantity:
14 both ends
Attachment Method:
Mounting hole
Pitch Diameter:
11.5000 inches
Teeth Quantity:
69
Bore Style:
Involute spline both ends
Spline Pitch Diameter:
1.4000 inches both ends
Hardness Rating:
90.0 rockwell superficial 15-n
Mounting Hole Type And Quantity:
3 plain transversely through face
Outside Diameter:
12.207 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
2.356 inches first end
Face Width:
0.500 inches
Bore Diameter:
1.500 inches both ends
Hub Diameter:
3.000 inches second end
First Groove Width:
0.073 inches first end
First Groove Diameter:
1.879 inches first end
Distance From End To First Groove:
1.523 inches first end
Mounting Hole Diameter:
0.281 inches axially through hub, first end
Bolt Hole Circle Diameter:
2.312 inches axially through hub, first end

NSN 3020-00-753-9882

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-13048 spec.



Material:
Steel
Material Specification:
Mil-s-13048 military specification single material response
Style Designator:
One protruding hub, one flush hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A27300